

PG2-B ABC

ABC POWDER FIRE EXTINGUISHER

CONSTRUCTION

BODY • Single piece, deep drawn aluminium body, externally painted with polyester resin.

VALVE • Valve body in acetalic resin. All external valve parts are in plastic material for maximum corrosion resistance.

CARTRIDGE • Disposable CO2 cartridge, deep drawn without welds, externally protected by zinc coating and passivation. Cartridge is housed in the dip tube.

EXTINGUISHING AGENT • ABC multipurpose dry powder. All parts in contact with the extinguishing agent are compatible with the same.

BRACKET • Plastic bracket specially designed for vehicle and marine use.

PACKING • Shrink-wrapping of the single piece and 6 pieces cardboard box.



ALUMINIUM

PG2-B ABC is an internal cartridge, dry powder fire extinguisher specially designed for car and marine use.

Wide operating temperature range $-30^{\circ}\text{C} + 60^{\circ}\text{C}$, ensures suitability for use in low-temperature countries.

Certified to the Pressure Equipment Directive PED 2014/68/EU, Marine Equipment Directive MED 2014/90/EU and CEN EN3.

Capacity is 2 kg.

FIRE CLASSES



13

89



PRODUCT CERTIFICATION



PG2-B ABC


ABC POWDER FIRE EXTINGUISHER

TECHNICAL CHARACTERISTICS

MODEL:	PG2-B ABC	INT	ING
FIRE RATINGS:	13A 89B C		
CHARGE:	2 kg \pm 3%		
PROPELLANT:	CO ₂ (carbon dioxide) 28 g		
EXTINGUISHING AGENT:	ABC dry powder		
DISCHARGE:	Discharge time :	~ 12 s	
CYLINDER:	Material of construction :	Aluminium alloy	
	Manufacturing process :	Deep drawing	
	External painting :	Polyester resin, minimum thickness 75 micron	
	Corrosion resistance :	480 h minimum according to ISO 9227:1990	
PRESSURE:	Operating pressure, 20 °C :	9 bar	
	Operating pressure, 60 °C :	11 bar	
	Operating pressure, -30 °C :	6 bar	
DIMENSIONS:	Overall height :	378 mm	
	Bottle OD :	108 mm	
WEIGHT:	Empty / Charged:	0,6 kg / 2,6 kg	
PACKING SPECIFICATIONS:	Standard packing :	4 pieces cardboard box	
	Carton size : B x L x H :	240 x 240 x 400 mm	
	Weight per carton :	11,4 kg	
	Pc/Pallet :	60 cartons (240 pieces)	
	Pallet size : B x L x H :	800 x 1200 x 1750 mm	
	Pallet volume :	1,68 m ³	
	Weight per pallet (net/gross):	684 kg / 704 kg	

© REPRODUCTION IS FORBIDDEN

32.039B.01.05.2017



① The valve is made up of acetal resin ensuring perfect corrosion protection.

② The spindle is made up of acetal resin for perfect sealing.

③ The spring does not interfere with the flow of the extinguishing agent: this permits a perfect discharge.

④ The large diameter of the safety pin ensures an easy grip even with work gloves.

⑤ Disposable CO₂ cartridge is housed in the dip tube.

⑥ The bracket is made of polypropylene: it may be fixed by screws on any surface, thanks to the different fastening points on the back of the bracket. The safety strip fastens the fire extinguisher to the support, making it perfectly stable, also in case of violent impact.

⑦ The single piece, deep drawn aluminium alloy body ensures maximum sealing and, thanks to its light weight, perfect handling.

* = NOT STANDARD BUT AVAILABLE ON REQUEST.
DATA AND CHARACTERISTICS SHOWN ON THIS TECHNICAL SPECIFICATION MAY BE MODIFIED IN ANY MOMENT WITHOUT NOTICE

ANAFGROUP

Via del Commercio, 4 - Torre d'Isola (Pavia)
Tel. 0382.4533 Fax. 0382.920279
info@anaf.eu | www.anaf.eu