

## PS2-P ABC

### ABC POWDER FIRE EXTINGUISHER

#### CONSTRUCTION

**BODY** • Single piece, deep drawn aluminium alloy body, externally painted with polyester resin, signal red to RAL 3000.

**VALVE** • The handy compact valve is ergonomically designed to guarantee an easy use with one hand. An inspectionable pressure gauge is provided. All external parts are either in plastic material or protected against corrosion.

**PROPELLANT** • The propellant gas is nitrogen. A small percentage of helium is added, to facilitate electronic leak detection.

**EXTINGUISHING AGENT** • ABC multi-purpose dry powder.

All parts in contact with the extinguishing agent are compatible with the same.

**BRACKET** • Plastic bracket specially designed for vehicle and marine use.

#### USE

Suitable for all fires (except metal fires).



**ALUMINIUM**

**PS2-P ABC** is a stored pressure, multi-purpose dry powder fire extinguisher with pressure gauge. It is ergonomically designed, easy to use and ideal for car and marine sectors. Wide operating temperature range  $-30^{\circ}\text{C} + 60^{\circ}\text{C}$ , ensures suitability for use in low-temperature countries. Certified to the Pressure Equipment Directive PED 2014/68/EU, Marine Equipment Directive MED 2014/90/EU and CEN EN3. 100% of the fire extinguishers are checked by an electronic helium leak detection system. Capacity is 2 kg.

#### FIRE CLASSES



13

89



#### PRODUCT CERTIFICATION



# PS2-P ABC


## ABC POWDER FIRE EXTINGUISHER

### TECHNICAL CHARACTERISTICS

|                         |                                |  |     |
|-------------------------|--------------------------------|--|-----|
| MODEL:                  | PS2-P ABC                      | INT  | ING |
| FIRE RATINGS:           | 13A 89B C                      |  |     |
| CHARGE:                 | 2 kg ± 3%                      |  |     |
| PROPELLANT:             | Nitrogen or nitrogen + helium  |  |     |
| EXTINGUISHING AGENT:    | ABC dry powder                 |  |     |
| DISCHARGE:              | Discharge time :               | ~ 12 s                                       |     |
| CYLINDER:               | Material of construction :     | Aluminium alloy                              |     |
|                         | Manufacturing process :        | Deep drawing                                 |     |
|                         | External painting :            | Polyester resin, minimum thickness 75 micron |     |
|                         | Corrosion resistance :         | 480 h minimum according to ISO 9227:1990     |     |
| PRESSURE:               | Operating pressure, 20 °C :    | 9 bar  |     |
|                         | Operating pressure, 60 °C :    | 11 bar                                       |     |
|                         | Operating pressure, -30 °C :   | 6 bar  |     |
|                         |                                |  |     |
| DIMENSIONS:             | Overall height :               | 378 mm                                       |     |
|                         | Bottle OD :                    | 108 mm                                       |     |
| WEIGHT:                 | Empty / Charged:               | 0,55 kg / 2,55 kg                            |     |
| PACKING SPECIFICATIONS: | Standard packing :             | 6 pieces cardboard box                       |     |
|                         | Carton size : B x L x H :      | 345 x 230 x 385 mm                           |     |
|                         | Weight per carton :            | 11,4 kg                                      |     |
|                         | Pc/Pallet :                    | 60 cartons (240 pieces)                      |     |
|                         | Pallet size : B x L x H :      | 800 x 1200 x 1750 mm                         |     |
|                         | Pallet volume :                | 1,68 m3                                      |     |
|                         | Weight per pallet (net/gross): | 684 kg / 704 kg                              |     |

© REPRODUCTION IS FORBIDDEN

12.659A.01.05.2017



① The handy compact valve is ergonomically designed to guarantee an easy use with one hand. The construction material of the cap ensures a perfect protection against corrosion. The safety button – PUSH 1 – and the operating button PUSH 2 – are clearly visible.

② The valve is made up of acetal resin ensuring perfect corrosion protection.

③ The spindle is made up of acetalic resin for perfect sealing.

④ The spring is made of Stainless Steel.

⑤ The yellow safety button is easy to check thanks to a visible seal on the top. It is marked: PUSH 1..

⑥ The shock-proof pressure gauge provides an accurate indication of pressure status of the extinguisher.

⑦ The bracket is made of polypropylene: it may be fixed by screws on any surface, thanks to the different fastening points on the back of the bracket. The safety strip fastens the fire extinguisher to the support, making it perfectly stable, also in case of violent impact.

⑧ The single piece, deep drawn aluminium alloy body ensures maximum sealing and, thanks to its light weight, perfect handling.

\* = NOT STANDARD BUT AVAILABLE ON REQUEST.  
DATA AND CHARACTERISTICS SHOWN ON THIS TECHNICAL SPECIFICATION MAY BE MODIFIED IN ANY MOMENT WITHOUT NOTICE

# ANAFGROUP

Via del Commercio, 4 - Torre d'Isola (Pavia)  
Tel. 0382.4533 Fax. 0382.920279  
info@anaf.eu | www.anaf.eu