

Temperature ranges

-80°C + 80°C



DESCRIPTION

ABC multi-purpose extinguishing dry powder capable to fight A,B, and C fires, certified according to EN615. We manufacture the extinguishing powder within our plants: the entire production cycle is 100% under our control. We respect the most stringent quality standards, sometimes stricter than the regulation

TECHNICAL DATA

FIRE CLASSES	ABC	
EXTINGUISHING AGENT	Monoammonium phosphate	
CHEMICAL COMPOSITION	Monoammonium phosphate	72% ± 3%
	Ammonium sulfate	22% ± 2%
	Additives	<10% ± 1%
APPARENT VOLUMETRIC MASS (EN615)	0,84 g/ml ± 0,07 g/ml	
GRANULOMETRY (EN615)	125 µm	10% ± 5%
	63 µm	34% ± 8%
	40 µm	49% ± 8%
	Method	Alpine Airjet Sieve
CONGLOMERATION RESISTANCE	No sieve residue at 425 µm	
HYDROPHOBIA	No complete absorption of water droplets	
WATER CONTENT	<0,2	
TEMPERATURE RANGES	-80°C + 80°C	
CONFORMITY	EN615 compliant	

PACKAGING

All our extinguishing powder bags are packed in our Italian factories, ready to be delivered all over the world. There are other packaging available on request with minimum order quantity



BAG 3 KG ABC POWDER



BAG 12,5 KG ABC POWDER



BAG 25 KG ABC POWDER



BIG BAG 1000 KG ABC POWDER

RANGE

Our wide range of extinguishing powder types:

Packaging	A32	A33	A35	A42	A52	A92	TOP	TOP PLUS
3 Kg	✓	✓	✓	✓	✓	✓	✓	✓
12,5 Kg	✓	✓	✓	✓	✓	✓	✓	✓
25 Kg	✓	✓	✓	✓	✓	✓	✓	✓
1.000 Kg	✓	✓	✓	✓	✓	✓	✓	✓