

Temperature ranges

-80°C + 80°C



## DESCRIPTION

TOP multi-purpose extinguishing dry powder capable to fight A,B, and C fires, certified according to EN615. Our TOP powder is with new additives and different granulometry, thus ensuring higher performances. We manufacture the extinguishing powder within our plants: the entire production cycle is 100% under our control. We respect the most stringent quality standards, sometimes stricter than the regulation

## TECHNICAL DATA

FIRE CLASSES	ABC	
EXTINGUISHING AGENT	Monoammonium phosphate	
CHEMICAL COMPOSITION	Monoammonium phosphate	13% ± 1%
	Ammonium sulfate	83% ± 3%
	Additives	<10% ± 1%
APPARENT VOLUMETRIC MASS (EN615)	0,84 g/ml ± 0,07 g/ml	
GRANULOMETRY (EN615)	125 µm	6% ± 5%
	63 µm	22% ± 8%
	40 µm	41% ± 8%
	Method	Alpine Airjet Sieve
CONGLOMERATION RESISTANCE	No sieve residue at 425 µm	
HYDROPHOBIA	No complete absorption of water droplets	
WATER CONTENT	<0,2	
TEMPERATURE RANGES	-80°C + 80°C	
CONFORMITY	EN615 compliant	

## PACKAGING

All our extinguishing powder bags are packed in our Italian factories, ready to be delivered all over the world. There are other packaging available on request with minimum order quantity



BAG 3 KG ABC POWDER



BAG 12,5 KG ABC POWDER



BAG 25 KG ABC POWDER



BIG BAG 1000 KG ABC POWDER

## RANGE

Our wide range of extinguishing powder types:

Packaging	A32	A33	A35	A42	A52	A72	A92	TOP PLUS
3 Kg	✓	✓	✓	✓	✓	✓	✓	✓
12,5 Kg	✓	✓	✓	✓	✓	✓	✓	✓
25 Kg	✓	✓	✓	✓	✓	✓	✓	✓
1.000 Kg	✓	✓	✓	✓	✓	✓	✓	✓