

PS4-HH ABC

Stored pressure

Powder

4 kg

Temperature ranges

-30° + 60°

ANAFGROUP



BODY

STEEL

Deep drawn 2-pieces mild steel cylinder, wire feed welded. Externally painted with polyester resin.

VALVE

ALUMINUM

Squeeze grip lever operated valve with aluminum body. The shock-proof pressure gauge provides an accurate indication of the pressure status of the extinguisher.

EXTINGUISHING AGENT

ABC multi-purpose dry extinguishing powder, certified according to EN 615.

PROPELLANT

The propellant gas is nitrogen. A small percentage of helium is added to allow electronic leak detection.

HOSE/HORN

The EPDM reinforced rubber hose guarantees perfect flexibility and resistance within the temperature range. Complete with nozzle.

PACKAGING

Single piece cardboard box, robust and suitable for transport.




Configuration

● Standard

○ On request

BRACKET



● Button holed wall bracket



○ Button holed wall bracket PG-M E FG-M



○ SUPPORTO PS4-HJ/HH TRASPORTO FILO

HOSE RINGS & PROTECTIVE BASE



● Hose holder Ø160



○ PROTECTIVE BASE D160 BLACK


PACKAGING



○ BOX 4KG/LT D160

Technical data

FIRE RATINGS	21A 144B C	
CHARGE	4 kg ±2%	
MATERIAL	STEEL	
CYLINDER	Manufacturing process	Deep Drawing
	External painting	Polyester Resin
	Corrosion resistance	480 H SECONDO ISO 9227:2017
EXTINGUISHING AGENT	ABC POWDER A32	
PROPELLANT	N2 + HE	
DISCHARGE	Discharge time	~ 17.7 s
PRESSURE	Operating pressure at 60 °C	15 bar
	Operating pressure at 20 °C	13 bar
	Operating pressure at -30 °C	11 bar
DIMENSIONS	Overall height	400 mm
	Bottle outer diameter	160 mm
WEIGHT	Empty / Charged	2.05 kg / 6.05 kg
PACKING SPECIFICATIONS	Standard packing	1 Pieces cardboard box
	Carton size (B x L x H)	470 x 180 x 180 mm
	Weight per carton	6.32 kg
	Pallet	72 Cartons
	Pallet size (B x L x H)	800 x 1200 x 1500 mm
	Pallet volume	1.44 m3
	Weight per pallet (net/gross)	450 kg / 470 kg



Spare parts list

Description	Code
SAFETY WIRE	00.005A.3220.00K0
BUTTON HOLED WALL BRACKET	00.005E.2900.00K0
WALL BRACKET	00.005E.2950.00K0
O-ring valve	00.033E.1100.01K0
HOSE HOLDER Ø160	00.241E.2800.00K0
SPINDLE	00.241E.6100.00K0
PRESSURE GAUGE	00.245E.4951.10K0
WALL BRACKET	00.752B.2900.10K0
ASSEMBLED HOSE	00.850D.2400.05K0
SUPPORT DE LANCE	00.850E.2960.01K0
METALLIC SUPPORT Ø160	00.850E.2970.00K0
BASE Ø160	00.850E.7100.01K0
SAFETY PIN	00.886E.5020.00K0
SCHRADER VALVE	00.886E.5100.00K0
TAPERED SPRING	00.886E.5200.00K0
DIP TUBE HOLDER	00.886E.5810.00K0
SAFETY LATCH	00.886E.6290.00K0
VALVE ASSEMBLY	00.886E.8100.01K0
TRANSPORT BRACKET	00.890D.2900.00K0
DIP TUBE	00.895D.5900.00K0